



DOUBLE SIDED ACRYLIC TAPE (CLEAR)

DATE OF TEST : 18/1/2017

ADHESIVE	TAPE COLOR(T) & RELEASE LINER (R.)	FORCE (N)	ELONGATION (%)	TOTAL THICKNESS (UM)
Silicone Acrylic	Clear (T) PE Red Liner (R.)	1.0 mm (T)

INITIAL TACK (# 7)	PEEL ADHESION (180°) (N/INCH)	TENSILE STRENGTH (N)	HOLDING POWER (PER HOUR)	HEAT RESISTING (MINUTE / °C)
.....	38N/in	24hr/in	-20°C ~120°C

(# = BALL) (UM = MICRON) (°C = CELSIUS) (≥ = GREATER THAN) (≤ = LESS THAN) (% = PERCENT) (N=NEWTON)

SHELF LIFE :

One year from date of receipt by customer . Please keep in cool dry place .

GENERAL DESCRIPTION :

Double Sided Acrylic Tape is a high performance, high tack bonding tape that is weather and water resistant.

APPLICATIONS

It is used for bonding and mounting of various parts in the automotive industry, electronics industry, furniture industry and the advertising, arts and graphics applications that require bonding.

Note : All information and recommendations are given by us in good faith on the basis of practical experience, but without warranty . The user shall determine the suitability of the product and the method of application for each specific use.

IDEALTAPE SDN BHD (969219-X)

NO : 7 JALAN BALAKONG JAYA 1 , TAMAN INDUSTRI BALALONG JAYA , 43300 BALAKONG SELANGOR MALAYSIA

TEL : 03-8964 0983 / 016-2100 268 FAX : 03-8964 0982 EMAIL : idealtapesb@gmail.com

WEBSITE : www.idealtape.com.my

