



DOUBLE SIDED PE FOAM TAPE (RED LINER & BLUE LINER)

DATE OF TEST : 18/1/2017

ADHESIVE	TAPE COLOR(T) & RELEASE LINER (R.)	FORCE (N)	ELONGATION (%)	TOTAL THICKNESS (UM)
Solvent	Black (T) Red or Blue (R.)	150%	1.0 mm (T)

INITIAL TACK (# 6)	PEEL ADHESION (180°) (N/INCH)	TENSILE STRENGTH (N)	HOLDING POWER (PER HOUR)	HEAT RESISTING (MINUTE / °C)
70 mm	12	12 (H)	10 °C - 80 °C

(# = BALL) (UM = MICRON) (°C = CELSIUS) (≥ = GREATER THAN) (≤ = LESS THAN) (% = PERCENT) (N=NEWTON)

SHELF LIFE :

One year from date of receipt by customer . Please keep in cool dry place .

GENERAL DESCRIPTION :

Double Sided PE Foam Tape is made of polyethylene foam (PE) as backing material which double coated with a pressure acrylic adhesive and PE-coated paper as release liner. As a description, PE Foam with IUPAC name of Polyethylene Foam is a firm and closed cell foam with cross-linkage. Hence, Double Sided PE Foam Tape is hard to return into its original shape after compressed by force. Typically with features of good resistance to higher temperature, ultra-violet light (UV) and solvent.

APPLICATIONS

- Widely applied on sign, nameplate, purchase display, book rack, photo frame and cable clip.
- Used as decorative material for craft making, artwork, origami making, gift wrapping and cushioning.
- Widely used for fastening of window mesh screen to protect against insects and mosquitoes.
- As glue replacement material for envelope sealing, scrapbook making, woodworking , advertising , car accessories and car number plates.

Note : All information and recommendations are given by us in good faith on the basis of practical experience, but without warranty . The user shall determine the suitability of the product and the method of application for each specific use.

IDEALTAPE SDN BHD (969219-X)

NO : 7 JALAN BALAKONG JAYA 1 , TAMAN INDUSTRI BALALONG JAYA , 43300 BALAKONG SELANGOR MALAYSIA

TEL : 03-8964 0983 / 016-2100 268 FAX : 03-8964 0982 EMAIL : idealtapesb@gmail.com

WEBSITE : www.idealtape.com.my

