



MASKING TAPE

(HIGH TEMPERATURE 999)

DATE OF TEST : 18-01-17

ADHESIVE	TAPE COLOR(T) & RELEASE LINER (R.)	FORCE (N)	ELONGATION (%)	TOTAL THICKNESS (UM)
Solvent Rubber	(T)= Buff	----	----	140

INITIAL TACK (# 7)	PEEL ADHESION (180°) (N /INCH)	TENSILE STRENGTH (N)	HOLDING POWER (PER HOUR)	HEAT RESISTING (MINUTE / °C)
35 mm	6.005	----	≥ 9	150 (1 hour)

(# = BALL) (UM = MICRON) (°C = CELSIUS) (≥ = GREATER THAN) (≤ = LESS THAN) (% = PERCENT) (N=NEWTON)

SHELF LIFE :

Eight months from date of receipt by customer . Please keep in cool dry place .

GENERAL DESCRIPTION :

Masking Tape is made of easy-to-tear crepe paper as carrier material which single coated with a solvent rubber adhesive of excellent tackiness.

Tearable, can be torn by hand due to design of easy-to-tear crepe paper as backing material.

APPLICATIONS :

Adhesive for high temperature application. Application such as automotive paint spraying,bandoleering,electroplating and etc.

Note : All information and recommendations are given by us in good faith on the basis of practical experience, but without warranty . The user shall determine the suitability of the product and the method of application for each specific use.

IDEALTAPE SDN BHD (969219-X)

NO : 7 JALAN BALAKONG JAYA 1 , TAMAN INDUSTRI BALAKONG JAYA , 43300 BALAKONG SELANGOR DARUL EHSAN , MALAYSIA .

TEL : 03-8964 0983 / 016-2100 268 FAX : 03-8964 0982 EMAIL : idealtapesb@gmail.com

WEBSITE : www.idealtape.com.my